

INTRODUCTION

The Addonics CF or CFast Duplicator is a family of fast and economical equipment for making copies of CF or CFast media. Choose from an array of models that allows you to duplicate 4, 5 or even 10 media at a time. The CF/CFast Duplicator is also easy to operate. Simply insert the source media into the source slot and target media with equal or larger capacity into the destination slots, then push the copy button to start the copying process. There is no complicated software to run.

About this model

This 1:5 CFast Duplicator model allows you to copy from one CFast card onto as many as five CFast cards at one time. It is a perfect equipment for content distribution using CFast media or cloning multiple copies of CFast card quickly without using a PC or running any special software



Support flash media copying options

CFast Duplicator			
Model	Product name	Source	Destination
CFASTD5	1:5 CFast Duplicator	CFast card	from 1 to 5 CFast cards
CFASTD4-2S	1:4 CFast Duplicator PRO	CF card (type I or II) or CFast card	from 1 to 4 CFast cards
CFASTD10-2S	1:10 CFast Duplicator PRO	CF card (type I or II) or CFast card	from 1 to 10 CFast cards

FEATURES

- Make copy from any type of CFast card
- Duplicate from one up to five CFast cards at one time
- Drive sanitization:
 - SECURE ERASE - HDD duplicator sends a WIPE command to the hard drive. This command fills 00 string to entire HDD (this feature may not be supported by some CFast and CF media)
 - OVERWRITE - One pass, 3 passes and 7 passes 5220.22-M. The duplicator writes a string of pattern over the entire disk one time, three times or seven times. 5220.22-M is the DoD standard for drive sanitization
- Completely standalone with no additional hardware or software required
- Copy speed up to 300 MB/sec depending on the performance of the media
- OS independent
- LCM control module provides a rich set of robust advanced configuration options (click Full LCD console feature list in this duplicator)
- Green LED for both source and destination slots to indicate media access

SPECIFICATIONS

- Writing mode : Sector to Sector
- Support up to 300 MB/sec transferring rate (actual transfer rate depends on the speed of flash media in the source and the destination slot)
- Sturdy metal frame construction
- One one CFast source slot
- Five CFast target slots
- LCD display with functional control panel
- Well ventilated for efficient air flow.
- Low noise high CFM ball bearing cooling fan
- Integrated 80W 110/240 auto-sense power supply
- Compact size - 7.48 x 10.63 x 6.5 inch (190 x 270 x 16.5 mm) (W x D x H)
- Weight: 8.15 lb (3.70 Kg)
- Operating environment: 0 - 60 degree C, 15% - 90% RH
- Storage environment: -40 - 90 degree C, 0% - 95% RH non-condensing
- 1 year warranty

