

INTRODUCTION

This ExpressCard CardBus adapter is a cost effective solution to add back the CardBus slot that is missing in many Notebook computer. Designed to turn any ExpressCard slot into a standard CardBus slot, with this adapter, Notebook computers that are equipped with ExpressCard only can now accept CardBus Wireless broadband card, LAN card, Panasonic P2&trade Card, CardBus eSATA adapter, video capture card and many other types of CardBus adapters.

The ExpressCard CardBus adapter is simple to use. Insert any CardBus device into the CardBus slot of ExpressCard CardBus adapter, then the ExpressCard end into the ExpressCard slot, the computer will instantly detect the new CardBus device. All there is needed is to follow the onscreen instructions to instal the drivers of the newly installed CardBus device.



* P2 cards are currently not supported under Mac OS X



FEATURES

- Connect any Cardbus card onto ExpressCard 34/54 card slot
- Great for connecting Cardbus devices onto Notebook computers that are only equipped with ExpressCard slot
- Supports Type I and Type II CardBus Cards
- Great for CardBus wireless broadband card, LAN card, P2 card, video capture card or any 32-bit CardBus adapter
- Hot-plug capability supported through ExpressCard connector
- No driver to install*
- RoHS compliant
- Compatible with Windows 98/ME, 2000, XP, 2003, Vista, Windows 7, Mac OS X 10.4.x

***Note:**

1. does not support 16-bit PCMCIA card such as ATA Flash, 4-in-1 DigiAdapter or CF DigiAdapter. Under Mac OS X, Panasonic P2 cards are currently not supported with this adapter.

2. "E" series Panasonic P2 cards not being compatible with the ExpressCard to Cardbus Adapter. Driver for the CardBus card inserted into this adapter still needs to be installed in order for the CardBus card to function properly. This driver is supplied by the manufacturer of the CardBus card.

SPECIFICATIONS

- Supports ExpressCard 34 and ExpressCard 54 form factor
- Supports 1-lane 2.5Gbps PCI Express
- Compliant with PCI Express Specification, revision 1.0a
- Supports Type I and Type II PC Cards
- Compliant with PC Card Standard 7.1
- PC 98/99 compliant
- Compatible with Windows 98/ME, 2000, XP, 2003, Vista, Windows 7, Mac OS X 10.4.x
- PC Card 32-bit Cardbus fully compliant
- Hot-plug capability supported through ExpressCard connector
- Dimension (W x D x H) - 65 x 125 x 10 mm.
- Weight - 40 grams
- 1 year warranty